REVISION HISTORY

DEVICE ORDER INFORMATION

ORDERABLE DEVICE	PACKAGING TYPE	STANDARD PACK QTY	PACKAGE MARKING	PINS	PACKAGE DESCRIPTION

ABSOLUTE MAXIMUM RATINGS

DESCRIPTION	MIN	MAX	UNIT

PIN CONFIGURATION



Figure 1. 8-Lead Plastic ESOP

SYMBOL	PARAMETER	TEST CONDITION	MIN	TYP	MAX	UNIT
Current Limit and Over Current Protection						
Enable and Soft Startup						

Bootstrap Voltage Regulator and Low Drop-out Operation

APPLICATION INFORMATION

Typical Application



Figure 11. SCT2650Q Design Example, 3.3V Output with Programmable UVLO

Design Parameters

Design Parameters	Example Value

Inductor Selection

Diode Selection

=

$$_1 = \frac{1}{2^{\quad 7}} = \frac{}{2^{\quad 7}}$$

$$_2 = \frac{1}{2} = \frac{}{2}$$

-
-
-

Table 3: Compensation Values for Typical Output Voltage/Capacitor Combinations at fsw=500KHz

Vout	L1	COUT	R4	C7	C6
2.5V	4.7uH	4*47uF	16.9K	4.7nF	68pF (optional)
3.3V	5.5uH	4*47uF	20K	4.7 nF	47pF (optional)
5V	7.8uH	4*47uF	33.2K	3.3nF	22pF (optional)
12V	10uH	4*47uF	53.6K	1nF	220pF
24V	15uH	4*47uF	105k	1nF	220pF

Inverting Power application

Application Waveforms













Application Waveforms(continued)









Layout Guideline

TAPE AND REEL INFORMATION